



湖南长富电子有限公司

地址: 长沙市岳麓区雷锋大道青山安置小区15栋

Tel:0731-88910304 Fax:0731-88910309

Model: LF20502CB/CSR/CSG/CSY

ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

PARAMETER		Red	Hi-Red	Green	Yellow	UNIT
Reverse voltage	Vr	5	5	5	5	V
Forward current	If	20	20	20	20	mA
Peak forward current	Ipeak	150	150	150	150	mA
Power dissipation	Pt	120	105	105	105	mW
Operating temperature	Ta	-40~+85	-40~+85	-40~+85	-40~+85	°C
Storage temperature	Tsta	-40~+85	-40~+85	-40~+85	-40~+85	°C

ELECTRICAL-OPTICAL CHARACTERISTICS(Ta=25°C)

Part NO.	Wavelength (nm)		Forward Voltage IF=20mA (v)		Reverse Current VR=5v(uA)	Luminous Intensity IF=20mA(ucd)
	λ_p	$\Delta\lambda$	TYP	MAX	MAX	TYP
LF20502CB	465	2.5	3.2	3.5	20	60000
LF20502CSR	640	5	2.0	2.5	20	30000
LF20502CSG	570	5	2.2	2.5	20	10000
LF20502CSY	585	5	2.1	2.4	20	10000

PACKAGE DIMENSION&INTERNAL CIRCUIT DIAGRAM:

